

Ocean Containers



General Purpose Containers

Suitable for any general cargo

	Maximum Inside Dimensions			Door Opening		Top Opening		Tare Weight (kg/lbs)	Cubic Capacity (m ³ /cu.ft.)	Maximum Payload (kg/lbs)
	L	W	H	W	H	L	W			
20' Dry Freight Container	5,895m 19'4 1/8"	2,350m 7'8 1/2"	2,392m 7'10 1/8"	2,340m 7'8 1/8"	2,292m 7'6 1/4"			2,250 kg 4,960 lbs	33,2 m ³ 1,172 cu.ft.	28,230 kg 62,240 lbs
40' Dry Freight Container	12,029m 39'5 1/2"	2,350m 7'8 1/2"	2,392m 7'10 1/8"	2,234m 7'8 1/2"	2,292m 7'6 1/4"			3,780 kg 8,330 lbs	67,7 m ³ 2,390 cu.ft.	26,700 kg 58,870 lbs



High Cube General Purpose Containers

Specifically for light, voluminous cargoes or those for excessive height (up to 2,67m)

	Maximum Inside Dimensions			Door Opening		Top Opening		Tare Weight (kg/lbs)	Cubic Capacity (m ³ /cu.ft.)	Maximum Payload (kg/lbs)
	L	W	H	W	H	L	W			
40' High Cube Container	12,024m 39'5 3/8"	2,350m 7'8 1/2"	2,697m 8'10 1/8"	2,340m 7'8 1/8"	2,597m 8'6 1/4"			4,020 kg 8,860 lbs	76,3 m ³ 2,694 cu.ft.	26,460 kg 58,340 lbs
45' High Cube Container	13,582m 44'6 1/2"	2,347m 7'8 1/4"	2,690m 8' 10"	2,340m 7' 8"	2,584m 8' 5 3/4"			4,110 kg 9,061 lbs	85,7 m ³ 3,026 cu.ft.	28,390 kg 62,589 lbs



Open Top Containers

Especially for overheight cargo, loading from top side; eg. - by crane, loading from door side: eg. - with cargo hanging from overhead tackle.


	Maximum Inside Dimensions				Top Opening		Tare Weight (kg/lbs)	Cubic Capacity (m ³ /cu.ft.)	Maximum Payload (kg/lbs)
	L	W	Middle	Side	L	W			
20' Open Top Container	5,895m 19' 4"	2,350m 7'8 1/2"	2,394m 7'10 1/4"	2,364m 7' 9"	5,895 m 19'4"	2,350 m 8 1/2"	2,100 kg 4,630 lbs	32,45 m ³ 1,146 cu.ft.	21,900 kg 48,280 lbs
40' Top Open Container	12,023m 39'5 3/8"	2,335m 7' 8"	2,378m 7'9 5/8"	2,318m 7'7 1/4"	12,023 m 39'5 3/8"	2,335 m 7'8"	3,800 kg 8,380 lbs	66,7 m ³ 2,354 cu.ft.	26,680 kg 58,820 lbs



Flats

Specifically for heavy-lifts and overwidth cargoes. Strong bottom construction with fixed endwalls (which allow bracing and lashing of cargo as well as stacking).

	Maximum Inside Dimensions			Door Opening		Top Opening		Tare Weight (kg/lbs)	Cubic Capacity (m ³ /cu.ft.)	Maximum Payload (kg/lbs)
	L	W	H	W	H	L	W			
20' Flat Rack Container	5,625m 18'5 3/8"	2,208m 7'2 7/8"	2,172m 7'1 1/2"					2,800 kg 6,170 lbs		21,200 kg 46,740 lbs
40' Flat Rack Container	11,712m 38'5 1/8"	2,232m 7'3 7/8"	1,981m 6'6"					4,750 kg 10,470 lbs		25,730 kg 56,730 lbs
40' Collapsible Flat Rack	11,660m 38'3 1/8"	2,200m 7'2 5/8"	2,245m 7'4 3/8"					5,700 kg 12,570 lbs		39,300 kg 86,640 lbs



Platforms

Especially for heavy loads and oversized cargo

	Maximum Inside Dimensions			Door Opening		Top Opening		Tare Weight (kg/lbs)	Cubic Capacity (m ³ /cu.ft.)	Maximum Payload (kg/lbs)
	L	W	H	W	H	L	W			
20' Steel Frame with Softwood Floor	6,058m 20'	2,438m 8'						2,100 kg 4,630 lbs		21,900 kg 48,280 lbs
40' Steel Frame with Softwood Floor	12,192m 40'	2,438m 8'						4,200 kg 9,260 lbs		40,800 kg 89,950 lbs